

PRODUCT SPECIFICATIONS FOR XQ60 TIER 4 FINAL



Rating Prime	47.5 ekW (60 kVA)
Frequency	60 Hz
Voltage	120 - 600V
Engine	Cat C3.4
Fuel	Diesel
Height - Without Trailer	65.3 in
Length - Without Trailer	106.5 in
Width - Without Trailer	41.3 in
Weight with Lube Oil and Coolant, Without Trailer	1305 kg
100% Load 60Hz	3.7 gal/hr
75% Load 60Hz	2.8 gal/hr
50% Load 60Hz	1.9 gal/hr
Sound Power @ 7 meters (23 feet) @ All Ratings	63 dB(A)

XQ60 TIER 4 FINAL STANDARD EQUIPMENT

CAT C3.4B DIESEL ENGINE

Heavy-duty.
After treatment

GENERATOR

1514P Frame

CONTROL PANEL

XQCP digital set mounted controller

CAT CONNECT REMOTE MONITORING

Provides package monitoring and management

COOLING SYSTEM

Package mounted radiator with vertical air discharge.
Filled from factory

CHARGING / STARTING SYSTEM

12V heavy duty starting motor and charging alternator c/w battery isolator

FUEL SYSTEM

24 hour dual wall fuel tank with 3 way directional valve for external supply

AIR FILTER

Cyclonic/paper with dust cup and service indicator

DISTRIBUTION

Single, robust enclosure for controls and distribution c/w 4 pole circuit breaker and safety cut off

STRUCTURE

Heavy Duty steel base frame with integral fuel tank.
Lifting frame and 4 point lift.
base frame is wider than enclosure to protect generator set during transportation

ENCLOSURE

Sound attenuating, galvanised steel enclosure with exceptional noise reduction performance

EXHAUST

Integrated spark arresting silencer

LUBE OIL

On engine primary and secondary oil filters. Filled from factory

GENERAL

Factory tested and inspected